

## Renewables

### Gum

Gum for Renewables is created during the production of vegetable oils, such as soybean oil, sunflower oil, palm oil and other oils commonly used in food and industrial processes. Water is added during the refining process of these oils to remove impurities. This results in a mixture of water, fatty acids, vegetable matter and other impurities, known as the co-product gum.

**Valid from 08 June 2023**

Downloaded on 24 June 2026

DM	53.0
Ash	5
Phosphor (P)	10.4
Nitrogen (N)	2
Potassium (K)	1.8
Biogas yield	550
Methane %	67

Levels are based on averages and stated in grams per kg of dry matter, unless stated otherwise. Changes in product composition are reserved.

### Logistics & Storage

Transport	liquid with tanker truck
Storage	Heated tank



**Loop Co-Products BV**  
 Parlevinkerweg 8  
 5928 NV Venlo  
 The Netherlands  
  
 www.loop.company  
 support@loop.company  
 +31(0)88 56 66 721

**IBAN:** NL55 RABO 0321 8217 85  
**BIC:** RABO NL2U  
**VAT. NL:** NL0095.32.488.13.01  
**VAT. BE:** BE0547739105  
**UST.ID:** DE2891.81.759  
**C.C. Venlo:** 1203 5225

**GMP+:** GMP018172  
**QS ID:** 4031735219906