

## Renewables

### Gum

Gum for Renewables is created during the production of vegetable oils, such as soybean oil, sunflower oil, palm oil and other oils commonly used in food and industrial processes. Water is added during the refining process of these oils to remove impurities. This results in a mixture of water, fatty acids, vegetable matter and other impurities, known as the co-product gum.

**Valid from 08 June 2023**

Downloaded on 15 December 2025

DM	53.0	Biogas yield	550
Ash	5	Methane %	67
Phosphor (P)	10.4		
Nitrogen (N)	2		
Potassium (K)	1.8		

Levels are based on averages and stated in grams per kg of dry matter, unless stated otherwise. Changes in product composition are reserved.

### Logistics & Storage

Transport liquid with tanker truck  
Storage Heated tank



**Loop Co-Products BV**  
Parlevinkerweg 8  
5928 NV Venlo  
The Netherlands  
  
www.loop.company  
support@loop.company  
+31(0)88 56 66 721

**IBAN:** NL55 RABO 0321 8217 85  
**BIC:** RABO NL2U  
**VAT. NL** NL0095.32.488.13.01  
**VAT. BE** BE0547739105  
**UST.ID:** DE2891.81.759  
**C.C. Venlo:** 1203 5225

**GMP+:** GMP018172  
**QS ID:** 4031735219906

